

Index

1.15 format 2-2
μ-law 1-2, 5-15, 5-23

A

A-law 1-2, 5-23
A/D converter 1-3, 1-10, 3-18, 8-1, 8-2,
..... 8-3, 8-4, 8-9, 10-14
AC (carry) 2-2, 2-5, 2-8, 2-13, 2-36
AC coupling 8-18
Accumulator 1-5
ADC, DAC interrupts 8-12
ADC 1-3, 1-10, 3-18, 8-1, 8-2, 8-3, 8-4, 8-9
ADC interface 13-10
Add with carry 2-8
Address generators 1-6, 1-7
Address pointers 1-7
ADSP-2181 9-13, 15-18
AF register 2-5
Alternate framing mode 5-13
ALU 1-1, 1-6, 2-5, 2-8, 3-21,
..... 3-24, 12-2, 12-6, 15-9, B-1
ALU arithmetic 2-2
ALU carry (AC) 2-26
ALU overflow (AV) 3-23, 3-24
ALU overflow latch mode 2-8, 2-9
ALU saturation mode 2-8, 2-9
ALU status 2-13
AN (negative) 2-2, 2-5, 2-13
Analog control register 8-5, 8-6, 8-8, 8-9, 8-10
Analog interface 1-3, 1-10
Analog loopback program 8-12
Analog-to-digital conversion 13-5
AQ (quotient) 2-5, 2-9, 2-10, 2-13
AR register 2-8, 2-22, 2-36
AR saturation 3-23, 3-24
Arithmetic formats 2-4
Arithmetic operation 3-24
Arithmetic shift 2-3, 2-22, 2-28
AS (sign) 2-5, 2-13
ASHIFT 2-31
Assembler 1-10
Assembler directives 12-10, 14-1

ASTAT 2-10, 2-13, 2-19, 2-24,
..... 2-26, 2-36, 3-21, 3-24, 12-5
Autobuffer service 5-39
Autobuffer timing 5-37
Autobuffering 5-3, 5-4, 5-26, 5-32, 5-38, 5-40,
..... 5-41, 8-1, 8-9, 8-10, 8-11, 8-12,
..... 8-13, 8-14, 8-15, 9-5, 9-23, 15-18
Autobuffer control register 5-27
AV (overflow) ... 2-2, 2-5, 2-8, 2-9, 2-13, 2-26, 2-36
AX0 register 2-5
AX1 register 2-5
AY0 register 2-5
AY1 register 2-5
AZ (zero) 2-5, 2-13

B

Bank select 3-23
Barrel shifter 1-6, 2-22
Base architecture 1-1, 1-6
BCR 9-13, 11-6, 11-7
BDMA 15-18
BDMA booting 9-13, 11-9
BDMA context reset 11-6, 11-7
BDMA interrupt 11-7
BEAD 11-4
BFORCE bit 10-16
BIAD 11-4
Binary multiplication C-3
Binary string 2-1
Bit-reverse addressing 1-7, 3-23, 4-2, 4-6, 14-18
Block exponent 2-26
Block floating-point 1-5, 14-19, C-5
BMODE pin 7-3, 7-16, 10-15, 11-9, 11-12
BMS 1-8, 7-16, 10-17
Boot address 10-18
Boot loading 13-2, 13-5
Boot loading sequence 10-17
Boot loading through the HIP 7-16
Boot memory 10-1, 10-15, 10-17
Boot pages 10-15
Boot operation 9-4
BPAGE 10-16

Index

Branching 3-1
BTYPE 11-9
Buffer length 4-5
Bus exchange 1-5, 1-8, 2-15, 4-1, 4-9, 12-6
Bus grant (**BG**) 3-18, 9-15
Bus request (**BR**) 5-38, 10-15, 10-21, 13-2
Buses 1-3, 1-8
BWAIT 10-17
BWCOUNT 9-13, 11-7
Byte memory 11-9

C

C Compiler 1-10
C language 14-3
CALL 3-4, 3-8, 3-9, 3-24
Carry (AC) 2-2, 2-5, 2-8, 2-13, 2-36
Carry-in (CI) 2-5
Chip enable 10-3
Circular buffer addressing ... 1-5, 1-7, 4-1, 4-3, 4-8
CLKIN 9-1, 9-3, 9-4
CLKOUT 9-2, 9-3, 9-4, 10-2
Clock frequency 8-9
Clock signals 9-1
Clock synchronization (SPORT) 5-35
Clock synchronization delay (SPORT) 5-34
CNTR register 3-4, 3-9, 12-4
Codec interface 13-5
Companding 1-2, 5-5, 5-15, 5-23, 5-24,
..... 5-25, 5-32, 5-36, 5-37, 5-42
Computation with data register move 15-7
Computation with memory read 15-6
Computation with memory write 15-6
Computational units 1-6, 3-23, 12-1, 12-6
Condition 3-20
Condition logic 3-3
Conditional instructions 3-24
Configuring interrupts 3-14
Context reset 11-7
Context switching 3-12
Continuous transmission 5-20
Control/status registers 1-12, E-1
Core architecture 1-5
Count stack 3-4, 3-5, 12-5
Counter expired (CE) 3-4, 3-6, 3-9
Cycle stealing 11-25

D

D/A 10-14
DAC 1-3
DAC interface 13-8
DAG1 1-7, 4-2, 12-2
DAG2 1-7, 3-3, 3-4, 3-8, 4-2, 12-2
Data address generators 4-1, 12-2
Data bus 4-1
Data memory 1-7, 1-8, 10-1
Data memory address bus 1-3, 1-8
Data memory data bus 1-3, 1-8
Data memory interface 10-10
Data memory read 15-6
Data structures 4-7
Data transfer 4-1
Denormalization 1-6
Denormalize 2-31
Derive block exponent 2-29
Derive exponent 2-22, 2-26
Development tools 14-2
Digital-to-analog conversion 13-5
Direct addressing 1-8
Divide primitives 2-9
Division exceptions B-1
Division 2-9
DIVQ 2-10, 2-11, B-1
DIVS 2-2, 2-9, 2-10, B-1
DMA 15-18
DMA bus 1-8, 10-1
DMD bus 1-8, 2-19, 2-22, 3-4,
..... 3-5, 3-20, 4-10, 10-1
DMD-PMD bus exchange 2-15, 4-1, 4-9, 4-10
DMOVLAY 10-31
DMS 1-8
DO UNTIL 3-4, 3-5, 3-6, 3-8, 3-9, 3-12, 12-5
DR input 5-2, 5-36
dreg 15-12, 15-14
DT output 5-2
Dual operand fetches 1-2, 1-5, 1-7

E

Edge-sensitive 3-15, 3-16, 3-18
Edge-sensitive interrupts 9-14
End-of-loop 3-7, 3-10
EPROM 1-4, 10-17

Index

EXP 2-33
EXPADJ 2-29
Exponent compare logic 2-22
Exponent detector 2-22, 2-26, 2-27
External address bus 1-3, 1-8
External clock 5-8, 9-21
External data bus 1-3, 1-8
External interrupts 9-14
External memory 5-38, 10-2
External SCLK 5-8
Extra cycles 15-18
EZ-ICE emulator 11-26

F

Fast fourier transform (FFT) 14-1, 14-11
Fast start-up 9-22
FIR filter 14-1, 14-4
Flag In (FI) 1-9, 3-24, 9-1
Flag Out (FO) 1-9, 9-1
Flag pins 9-15
Floating-point 2-33
Fractional mode 2-2, 2-3, 3-23, 3-24, C-1, C-4
Frame synchronization .. 5-2, 5-5, 5-10, 5-11, 5-12,
..... 5-14, 5-15, 5-30, 5-34, 9-23
Framing 5-3, 5-16
Full duplex operation 5-34

G

GO mode 3-23, 3-24, 5-38

H

HACK 7-3, 7-7, 7-9
Harvard architecture 1-2, 10-1
HDR overwrite mode 7-7, 7-9
HDR registers 7-4, 7-5, 7-6, 7-7
HI-extend (HIX) 2-26, 2-36
HI/LO reference signal 2-22, 2-24
HIP configuration modes 7-3
HIP data registers 3-15, 7-4, 7-5, 7-6, 7-7
HIP during powerdown 9-24
HIP interrupt 3-18, 7-9, 7-10, 7-11
HIP pin summary 7-2
HIP read interrupt 7-4
HIP status registers 7-6
HIP status synchronization 7-8
HIP timing 7-12, 7-13, 7-14, 7-15
HIP write interrupt 7-4
HMASK register 3-15, 7-4, 7-10, 7-11, 12-8

HMD0 7-3, 7-4
HMD1 7-4
Hold offs 11-25
Host 1-2
Host data bus 7-4
Host handshaking 7-7
Host interface port (HIP) ... 1-2, 1-9, 3-15, 7-1, 7-4,
..... 9-4, 10-15, 12-2, 13-13
Host interface timing 7-11
Host read strobe 7-4
Host write strobe 7-4
HSEL 7-3
HSIZE 7-3, 7-11
HSR registers 7-4, 7-5, 9-25

I

I registers 4-2, 4-3, 5-26, 5-28, 8-14, 12-2
IACK 11-12, 11-13, 11-25
ICNTL register 3-14, 3-15, 3-16, 3-20, 9-14, 12-4
IDLE instruction 3-7, 3-10, 5-26, 9-15,
..... 9-19, 9-26, 9-30
IDMA 11-12, 15-18
IDMA booting 11-24
IDMA control register 11-14, 11-15, 11-16
IDMA hold offs 11-25
IFC register 3-14, 3-18, 3-20, 12-4
IIR filter 14-1, 14-6
IMASK register 3-14, 3-15, 3-16, 3-19,
..... 3-20, 7-10, 8-12, 9-14, 12-4
Immediate shifts 2-30
Indirect addressing 1-8, 4-3, 12-2
Indirect jumps 12-2
Input formats 2-18
Input registers 1-7
Instruction completion latencies 5-38, 15-18
Instruction set 15-1, A-1
Integer 3-23, 3-24, C-1
Integer mode 2-3, C-4
Internal buses 1-8
Internal memory 1-2
Internal oscillator 9-22
Interrupt control register 3-15
Interrupt controller 3-1, 3-3, 3-11
Interrupt force & clear register 3-15, 3-18
Interrupt latencies 3-19, 5-42
Interrupt mask register 3-16
Interrupt nesting 3-16
Interrupt request 5-40, 9-1, 9-14
Interrupt sensitivity 9-14

Index

Interrupt service 3-12, 3-14, 3-16,
..... 3-18, 3-20, 5-39
Interrupt vector 3-11, 3-12, 3-13,
..... 3-14, D-1, D-2, D-3
Interrupts 1-9, 3-4, 3-16, 9-24, 9-30, 12-4, 12-11
Interrupts pending 3-18
Interval timer 3-18, 3-23, 3-24
INVRFSS 5-14, 5-16, 5-32
INVTDV 5-32
INVTFS 5-14, 5-16, 5-32
IRFS 5-11, 5-32
IRO0 1-9, 3-11, 5-3, 9-14
IRO1 1-9, 3-11, 5-3, 9-14
IRO2 5-38, 9-14
ITFS 5-11

J

JUMP 3-8, 3-9, 3-24

L

Length (L) registers 4-1, 4-3, 4-4, 12-2
Level-sensitive interrupts 3-15, 9-14
Linker 14-3
Logical shift 2-3, 2-22, 2-28
Loop 3-5, 3-6, 3-7, 3-9
Loop comparator 3-3, 3-5, 3-6, 3-10
Loop counter 1-7, 3-4, 3-5, 12-4
Loop stack 3-4, 3-5, 3-6, 3-7, 3-22, 12-5
LSHIFT 2-31

M

M registers 4-1, 4-2, 4-3, 5-26, 5-28, 8-14, 12-2
MAC 1-6, 2-13, 2-15, 3-21,
..... 12-2, 12-6, 15-9, 15-10
MAC arithmetic 2-3
MAC input/output registers 2-18
MAC operations 2-16
MAC overflow 2-19
MAC saturation 2-19
Matrix multiply 14-1, 14-9
Memory address 3-3
Memory interface 10-2, 10-37, 12-2, 12-7
Memory read 10-3
Memory wait states 3-18
Memory write 10-3, 10-24
Memory-mapped registers 12-1
MF register 2-15, 2-20
Miscellaneous instructions 15-16
MMAP 7-16, 10-5, 10-6, 10-15
Mode bits 12-5

Mode control 12-5, 15-16
Mode status register (MSTAT) 3-12, 3-22
Modify (M) registers 4-1, 4-2, 4-3, 5-26, 5-28
Modulo addressing 4-1, 4-4
Modulus logic 4-3
MOVE instructions 15-13
MR register 2-13, 2-15, 2-16, 2-18, 2-20, 2-22
MR0 register 2-13, 2-15, 2-18
MR1 register 2-13, 2-15, 2-19, 2-20
MR2 register 2-13, 2-15, 2-19, 2-20
MSTAT 1-7, 2-8, 2-9, 2-16, 2-24, 3-12,
..... 3-14, 3-20, 3-22, 4-2, 6-1, 12-5
Multichannel 1-2, 1-8, 5-3, 5-5, 5-30
Multichannel frame delay 5-32
Multichannel length bit 5-31
Multichannel mode 5-30, 5-31, 5-32
Multichannel operation 5-32, 5-33
Multichannel setup 5-30
Multichannel transfer 5-32, 5-33
Multifunction instructions 1-4, 15-7, 15-19
Multiplication 2-13
Multiplier 2-18
Multiplier result format 2-17
Multiplier/accumulator 1-6, 2-13, 2-15, 3-21
Multiply/add 1-6
Multiply/subtract 1-6
Multiprecision capability 2-8
Multiprocessing 9-4
MV 2-13, 2-19
MX register file 2-15
MX0 register 2-15
MX1 register 2-15
MY register file 2-15
MY0 register 2-15
MY1 register 2-15

N

Nested loops 3-8
Nesting 3-15, 3-16
Next instruction address 3-3, 3-4, 3-7, 3-10
Normal framing mode 5-13
Normalize 2-22, 2-28, 2-33
Normalize modifiers 2-35
Numeric formats C-1

O

Off-chip memory accesses 15-18
On-chip memory 1-2
On-chip peripherals 1-2, 1-8
Opcodes A-1
Operating mode 3-22

Index

Operation during powerdown 9-23
OR/PASS logic 2-22, 2-24
Output enable 10-3, 10-24
Output registers 1-7
Overflow (AV)... 2-2, 2-5, 2-8, 2-9, 2-13, 2-26, 2-36
Overwrite bit 9-24
Overwrite mode 7-7, 7-9
OWRCNTR 3-5

P

Page length 10-15, 10-18
PASS 2-32, 2-33
PC 3-4
PC incrementer 3-3
PC stack 3-3, 3-4, 3-6, 3-10, 3-11,
..... 3-22, 12-5, 15-84, 15-85
PDFORCE 9-18
Period register 6-1
Periodic interrupts 6-1
PMA bus 1-8, 3-3, 3-4, 3-8, 10-1, 10-3
PMD bus 1-8, 10-1, 10-3
PMD-DMD bus exchange... 1-5, 1-8, 2-15, 4-1, 4-9
PMOVLAY 10-26
PMS 1-8, 10-3, 10-24
Polled operation 7-7
PORT directive 10-14
Powerdown 8-9, 9-17, 9-20, 9-30
Powerdown acknowledge 9-29
Powerdown control register 9-18, 9-20
Powerdown force control bit 9-19
Powerup 9-20
Powerup boot 10-16
Primary registers 2-7
Processor states 9-2
Program counter 3-4
Program flow control 15-14, 15-15
Program memory 1-8, 10-1
Program memory configuration 10-5
Program memory data bus 4-9
Program memory interface 10-3
Program memory map 10-5, 10-6
Program memory read 10-3, 15-6
Program memory write 10-3
Program sequencer 3-1, 3-5, 12-2, 12-4
Programming model 12-1
PUCR 9-18
PWAIT 10-5
PWD pin 9-19
PWDACK pin 9-29
PX registers 1-5, 4-9, 4-10

Q

Quotient format 2-12

R

R bus 1-6, 2-15, 2-18, 2-22
RAM 10-6
Read operation 15-12
Receive companding latency 5-40
Receive frame sync 5-11, 5-12, 5-30
Receive interrupt (SPORT) 5-4, 5-36
Receive register 5-6
Receive word enables 5-31
Receiving data 5-6
reg 15-12, 15-14
Register indirect JUMPs 3-8
Register notation 15-20
Registers 12-1, 12-3
RESET 9-1, 9-4, 9-21, 9-25
Result bus 1-6
Return 3-7, 3-10
RFS 5-2, 5-11, 5-12, 5-30
RFS DIV 5-12
RFS DIV 12-7
RFSR 5-10, 5-11
RFSW 5-13
Rounding mode 2-20
RTI instruction 3-11, 9-15, 9-30
RX register 5-2, 5-4, 5-32, 5-36
RX0 register 5-6, 5-32
RX1 register 5-6

S

Saturation 2-13
SB register 2-22, 2-29
SCLK 5-1, 5-12, 5-13, 5-15, 5-16
SCLK frequencies 5-9
SCLK pin 5-9
SCLK0 5-34
SCLK1 5-34
SCLKDIV 5-9, 12-7
SE register .. 2-22, 2-24, 2-26, 2-30, 2-31, 2-33, 2-34
Secondary register 3-12
Serial clock 5-1, 5-5, 5-8, 5-34, 5-38
Serial clock frequencies 5-8
Serial port autobuffering 5-42
Serial ports 1-8, 5-1, 5-38, 9-5, 9-23, 12-7,
..... 13-5, 13-6, 13-7, 13-8, 13-10
Serial word length 5-5, 5-9
Shifter 1-6, 3-21, 12-2, 15-9, 15-11

Index

Shifter arithmetic 2-3
Shifter array 2-22
Shifter input/output registers 2-28
Shifter operations 2-28
Shifter sign 2-26
SI register 2-22, 2-23
Signed numbers 2-1
Sine approximation 14-7
SLEN 5-10, 5-16, 5-31, 5-32
Software examples 14-1
Software reboot 10-16
SPORT 1-8, 3-18, 5-1, 5-3, 5-6, 9-23
SPORT control register 5-8, 5-10, 5-11, 5-13,
..... 5-14, 5-16, 5-23, 5-31
SPORT enable 5-7
SPORT interrupts 5-3, 5-34, 5-41
SPORT multichannel frame delay 5-31
SPORT programming 5-4
SPORT timing 5-34
SPORT configuration 5-5
SPORT0 5-1, 5-5, 5-15, 5-16, 5-30,
..... 8-13, 12-7, 13-6, 13-7
SPORT0 configuration registers 5-5
SPORT0 control register 5-30
SPORT0 multichannel word enable registers . 5-32
SPORT1 5-5, 5-30, 8-9,
..... 8-13, 9-14, 9-15, 12-2
SPORT1 alternate configuration 5-8
SPORT1 configuration registers 5-5
SR register 2-22, 2-23
SR0 register 2-22, 2-24
SR1 register 2-22, 2-24
SSTAT 12-5
Stacks 3-4, 12-5
Start-up delay 9-20
Start-up time 9-21
Startup timing 5-38
Status bits 3-21, 12-5
Status condition 3-6, 3-25
Status logic 3-4
Status registers 3-15, 3-20
Status stack 3-16, 3-20, 3-22, 12-5
Stolen cycles 15-18
Subroutine 3-9
Subtract with borrow 2-8
Synchronization delay 9-3
Synchronization (serial clk to processor clk) ... 5-38
System Builder 1-10
System Control Register 9-14, 9-15,
..... 10-17, 15-12, E-1
System interface 9-1

T

T1 interface 5-31
TCOUNT 6-1, 6-2, 6-3, 6-4, 12-6
TDV 5-32
Termination condition 3-6, 3-10
TFS 5-2, 5-11, 5-12, 5-30
TFS0 5-30
TFSR 5-10, 5-11
TFSW 5-13
Time-division multiplexed 5-30
Timer 3-18, 3-23, 3-24, 6-1, 9-5, 12-2, 12-6
Timer interrupt 3-19, 6-1
Timer operation 6-3
Timer registers 6-1, 6-2
TOPPCSTACK .. 3-4, 3-25, 3-26, 3-27, 15-84, 15-85
TPERIOD 6-1, 6-2, 6-3, 6-4, 12-6
Transmit data valid 5-32
Transmit frame sync 5-11, 5-12
Transmit interrupt (SPORT) 5-4, 5-36
Transmit register 5-6
Transmit word enables 5-32
Transmitting data 5-6
TSCALE 6-1, 6-2, 6-3, 6-4, 12-6
Twos-complement 2-1, 2-18, 2-33, C-1, C-4
TX register 5-2, 5-4, 5-35
TX0 register 5-6
TX1 register 5-6

U

Underflows 2-8
Unsigned 2-1, 2-18, C-1

W

Word length 5-3, 5-9, 5-32
Write enable 10-3
Write operation 15-12

X

XTAL pin 9-1, 9-21, 9-22
XTALDELAY 9-18, 9-20
XTALDIS 9-18

Z

Zero-overhead looping 1-5, 3-1